

# MyPBX SOHO

## Embedded Hybrid IP-PBX for Small Business



MyPBX SOHO is a standalone embedded hybrid PBX specially designed for small businesses and offices up to 30 users which offers the flexibility of integration of ISDN, PSTN lines, and VoIP trunks. In this way, the company's communication costs would be greatly reduced by taking advantage of latest VoIP technology while the traditional reliability is guaranteed.

- **Easy to use**  
Easy to deploy and manage via web-based configuration interface
- **Robust all-in-one features**  
Deliver enterprise-class communication features and functionality to SMBs
- **Modular Technology**  
Customizable combination of FXO, FXS, BRI, modules
- **Match your IP phone**  
Perfect interoperability with mainstream IP Phone
- **Speak your language**  
Multi-languages web GUI and voice prompts
- **No future licensing fees**  
Scalable with plug-and play ease without licensing
- **Enhanced security**  
Secure your communication from attack and abuse with firewall.
- **Energy Saving**  
Low power consumption for your green office



## Basic Features

- Automated Attendant (IVR)
- Attend Transfer
- Blind Transfer
- Blacklist
- Call Detail Records (CDR)
- Call Forward
- Call Parking
- Call Pickup
- Call Routing
- Call Waiting
- Caller ID
- Conference
- Do Not Disturb (DND)
- Follow me
- Intercom/Zone Intercom
- Music on Hold
- Music on Transfer
- Queue
- Ring Group
- Skype Integration (Skype Connect)
- Speed Dial
- Voicemail(4000 minutes)
- Voicemail to email
- Voicemail Forwarding

## Advanced Features

- Direct Inward System Access (DISA)
- Distinctive Ringtone
- Dial by Name
- One touch recording
- Phone Provisioning for Cisco, Yealink, Snom, Aastra, Polycom IP Phone
- Qos (voice quality)
- Route by Caller ID
- Spy functions (Normal Spy, Whisper Spy, Barge Spy)

## Security

- Firewall
- SIP TLS transport

## Multiple Language

- System voice prompt: American English, Australian English, Chinese, Dutch, French, Canadian French, German, Greek, Hungarian, Italian, Polish, Portuguese, Brazilian Portuguese, Russian, Spanish, Mexican Spanish, Turkish, Thai, Korean , Persian
- Web GUI: English, Chinese Simplified, Portuguese, Spanish, Russian, Hebrew, Turkish, French, Italian, Polish, Romanian, Thai, Korean, German, Dutch

## Internet

- DHCP server
- DDNS
- 1 LAN port (10/100Mbps): Static IP, DHCP client
- VLAN

## Hardware Interface

- 1 LAN port
- Up to 4 FXO ports (O2 module based)
- Up to 4 FXS ports (S2 module based)
- Up to 4 BRI ports (B2 module based)
- LED: Red for FXO, Green for FXS , Orange for BRI

## System capacity

- 30 IP phone users
- 8 concurrent calls
- 512 MB Onboard Flash
- 64 MB Onboard RAM
- Protocol: SIP (RFC3261)
- Transport: UDP, TCP, TLS
- DTMF: RFC2833, SIP INFO, In-band
- Codec: G.711 (a-law, u-law), G.722, G.726, G.729 A, GSM, Speex, ADPCM, H261, H263, H263p, H264, MPEG4

## Environmental

- Size: 193x153x30mm
- Weight: 500g
- Power Supply: AC 100~240V, 50~60Hz , DC 12V, 1A
- Operation Range: 0°to 40°C, 32° to 122° F
- Storage Range: -20° to 65°C, 4° to 149° F
- Humidity: 10-90% non-condensing



Yeostar

Enterprise Communication

Yeostar Technology Co.,Ltd

Tel: +86-592-5503309

Fax: +86-592-5503307

E-mail: sales@yeostar.com

Website: www.yeostar.com